


# OBG

## Aufhängebügel außenliegend mittig



|        | Max. Belastung (in daN) |
|--------|-------------------------|
| OBG050 | 200                     |
| OBG075 | 200                     |
| OBG100 | 200                     |
| OBG150 | 200                     |
| OBG200 | 200                     |
| OBG250 | 150                     |
| OBG300 | 150                     |
| OBG400 | 90                      |

| Referenz      | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦  | Einheit |
|---------------|---------|---------|------------|---------|--------|----|---------|
| <b>OBG050</b> | 64      | 55      |            |         | 0,100  | 12 | STK     |
| <b>OBG075</b> | 64      | 80      |            |         | 0,130  | 12 | STK     |
| <b>OBG100</b> | 64      | 105     |            |         | 0,140  | 12 | STK     |
| <b>OBG150</b> | 64      | 155     |            |         | 0,190  | 12 | STK     |
| <b>OBG200</b> | 64      | 205     |            |         | 0,220  | 12 | STK     |
| <b>OBG250</b> | 64      | 255     |            |         | 0,270  | 12 | STK     |
| <b>OBG300</b> | 64      | 305     |            |         | 0,310  | 6  | STK     |
| <b>OBG400</b> | 64      | 405     |            |         | 0,390  | 6  | STK     |

Zu befestigen mit Gewindestange TIM8 oder TIM10.