



# ZCL

## Z-Support klipsbar



|        | Max. Belastung (in daN) |
|--------|-------------------------|
| ZCL100 | 150                     |
| ZCL150 | 150                     |
| ZCL200 | 120                     |
| ZCL300 | 105                     |
| ZCL400 | 90                      |
| ZCL500 | 80                      |
| ZCL600 | 65                      |

| Referenz      | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦  | Einheit |
|---------------|---------|---------|------------|---------|--------|----|---------|
| <b>ZCL100</b> | 14      | 60      |            | 180     | 0,135  | 12 | STK     |
| <b>ZCL150</b> | 14      | 60      |            | 230     | 0,165  | 12 | STK     |
| <b>ZCL200</b> | 14      | 60      |            | 280     | 0,210  | 12 | STK     |
| <b>ZCL300</b> | 14      | 60      |            | 380     | 0,265  | 12 | STK     |
| <b>ZCL400</b> | 14      | 60      |            | 480     | 0,315  | 12 | STK     |
| <b>ZCL500</b> | 14      | 60      |            | 580     | 0,365  | 12 | STK     |
| <b>ZCL600</b> | 14      | 60      |            | 680     | 0,415  | 12 | STK     |

Zu befestigen mit Gewindestange TIM6 oder TIM8.

Max. Belastung (in daN): Gleichmäßig verteilte Last über die gesamte Breite des Auslegers.

Gewindestange separat zu bestellen.