

## D Universaldeckel



Geeignet für horizontale und vertikale Strecken.

Referenz	Oberfläche	↑ mm	↔ mm	→  ← mm	↔ mm	kg/m	📦	Einheit
<b>D050</b>	SZ	10	50		3000	0,328	30	M
<b>D075</b>	SZ	10	75		2000	0,446	20	M
<b>D100</b>	SZ	10	100		2000	0,564	20	M
<b>D100.3</b>	SZ	10	100		3000	0,563	300	M
<b>D150</b>	SZ	10	150		2000	0,799	20	M
<b>D200</b>	DF	10	200		2000	1,035	20	M
<b>D200.3</b>	SZ	10	200		3000	1,035	300	M
<b>D250</b>	SZ	10	250		2000	1,481	20	M
<b>D300</b>	SZ	10	300		2000	1,756	20	M
<b>D400</b>	SZ	10	400		2000	2,960	20	M
<b>D500</b>	SZ	10	500		2000	3,667	2	M
<b>D600</b>	SZ	10	600		2000	4,373	2	M
<b>ZMD050</b>	DF	10	50		3000	0,328	30	M
<b>ZMD075</b>	DF	10	75		2000	0,446	20	M
<b>ZMD100</b>	DF	10	100		2000	0,564	20	M
<b>ZMD150</b>	DF	10	150		2000	0,799	20	M
<b>ZMD200</b>	DF	10	200		2000	1,035	20	M
<b>ZMD250</b>	DF	10	250		2000	1,481	20	M
<b>ZMD300</b>	DF	10	300		2000	1,756	20	M
<b>ZMD400</b>	DF	10	400		2000	2,960	20	M
<b>ZMD500</b>	DF	10	500		2000	3,667	2	M
<b>ZMD600</b>	DF	10	600		2000	4,373	2	M

### Zu befestigen mit:



Deckelklemme  
klipsbar  
DCL

Deckelklemme  
unverlierbar  
klipsbar  
DCO

Deckel mit Breite > 400 mm werden mit diagonalen Verstärkungsrippen geliefert.

### Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender