

KLLVB

Fallstück für KLL



Zu befestigen mit:



Flachrundkopfschraube mit
Flanschmutter
VM

Radius: 300 mm

| Referenz | Oberfläche | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Einheit |
|-----------------------|------------|---------|---------|------------|---------|--------|---|---------|
| KLLVB60.150 | - | 60 | 146 | | | 1,528 | 1 | STK |
| KLLVB60.200 | - | 60 | 196 | | | 1,629 | 1 | STK |
| KLLVB60.300 | - | 60 | 296 | | | 1,830 | 1 | STK |
| KLLVB60.400 | - | 60 | 396 | | | 2,032 | 1 | STK |
| KLLVB60.450 | - | 60 | 443 | | | 2,133 | 1 | STK |
| KLLVB60.500 | - | 60 | 496 | | | 2,234 | 1 | STK |
| KLLVB60.600 | - | 60 | 596 | | | 2,435 | 1 | STK |
| KLLVB60.750 | SZ | 60 | 750 | 1,25 | | 2,501 | 1 | STK |
| KLLVB60.800 | SZ | 60 | 800 | 1,25 | | 2,588 | 1 | STK |
| KLLVB60.900 | SZ | 60 | 900 | 1,25 | | 2,762 | 1 | STK |
| KLLVB110.150 | - | 110 | 145 | | | 2,934 | 1 | STK |
| KLLVB110.200 | - | 110 | 196 | | | 2,755 | 1 | STK |
| KLLVB110.300 | - | 110 | 296 | | | 2,956 | 1 | STK |
| KLLVB110.400 | - | 110 | 396 | | | 3,158 | 1 | STK |
| KLLVB110.450 | - | 110 | 445 | | | 3,259 | 1 | STK |
| KLLVB110.500 | - | 110 | 496 | | | 3,360 | 1 | STK |
| KLLVB110.600 | - | 110 | 596 | | | 3,561 | 1 | STK |
| KLLVB110.750 | - | 110 | 750 | | | 3,863 | 1 | STK |
| KLLVB110.800 | SZ | 110 | 800 | 1,25 | | 3,549 | 1 | STK |
| KLLVB110.900 | - | 110 | 900 | | | 4,165 | 1 | STK |
| ZMKLLVB60.150 | DF | 60 | 150 | 1,25 | | 1,455 | 1 | STK |
| ZMKLLVB60.200 | DF | 60 | 200 | 1,25 | | 1,542 | 1 | STK |
| ZMKLLVB60.300 | DF | 60 | 300 | 1,25 | | 1,716 | 1 | STK |
| ZMKLLVB60.400 | DF | 60 | 400 | 1,25 | | 1,891 | 1 | STK |
| ZMKLLVB60.450 | DF | 60 | 450 | 1,25 | | 1,978 | 1 | STK |
| ZMKLLVB60.500 | DF | 60 | 500 | 1,25 | | 2,065 | 1 | STK |
| ZMKLLVB60.600 | DF | 60 | 600 | 1,25 | | 2,239 | 1 | STK |
| ZMKLLVB60.750 | DF | 60 | 750 | 1,25 | | 2,501 | 1 | STK |
| ZMKLLVB60.800 | DF | 60 | 800 | 1,25 | | 2,588 | 1 | STK |
| ZMKLLVB60.900 | DF | 60 | 900 | 1,25 | | 2,762 | 1 | STK |
| ZMKLLVB110.150 | DF | 110 | 150 | 1,25 | | 2,416 | 1 | STK |
| ZMKLLVB110.200 | DF | 110 | 200 | 1,25 | | 2,503 | 1 | STK |
| ZMKLLVB110.300 | DF | 110 | 300 | 1,25 | | 2,677 | 1 | STK |
| ZMKLLVB110.400 | DF | 110 | 400 | 1,25 | | 2,851 | 1 | STK |
| ZMKLLVB110.450 | DF | 110 | 450 | 1,25 | | 2,939 | 1 | STK |
| ZMKLLVB110.500 | DF | 110 | 500 | 1,25 | | 3,026 | 1 | STK |
| ZMKLLVB110.600 | DF | 110 | 600 | 1,25 | | 3,200 | 1 | STK |
| ZMKLLVB110.750 | DF | 110 | 750 | 1,25 | | 3,462 | 1 | STK |
| ZMKLLVB110.800 | DF | 110 | 800 | 1,25 | | 3,549 | 1 | STK |
| ZMKLLVB110.900 | DF | 110 | 900 | 1,25 | | 3,723 | 1 | STK |

Min. Anzahl Schrauben und Muttern VM6.10: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender

