

KLM100VB45

Fallstück 45° für KLM100



Radius: 600 mm

Referenz	Oberfläche	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	Einheit	Einheit
KLM100VB45.150	SZ	100	158			2,637	1	STK
KLM100VB45.200	SZ	100	208			2,714	1	STK
KLM100VB45.300	SZ	100	308			2,868	1	STK
KLM100VB45.400	SZ	100	408			3,021	1	STK
KLM100VB45.450	SZ	100	458			3,098	1	STK
KLM100VB45.500	SZ	100	508			3,175	1	STK
KLM100VB45.600	SZ	100	608			3,329	1	STK
KLM100VB45.750	SZ	100	758			3,559	1	STK
KLM100VB45.800	SZ	100	808			3,636	1	STK
KLM100VB45.900	SZ	100	908			3,790	1	STK
KLM100VB45.1000	SZ	100	1008			3,943	1	STK
ZMKLM100VB45.150	DF	100	158			2,637	1	STK
ZMKLM100VB45.200	DF	100	208			2,714	1	STK
ZMKLM100VB45.300	DF	100	308			2,868	1	STK
ZMKLM100VB45.400	DF	100	408			3,021	1	STK
ZMKLM100VB45.450	DF	100	458			3,098	1	STK
ZMKLM100VB45.500	DF	100	508			3,175	1	STK
ZMKLM100VB45.600	DF	100	608			3,329	1	STK
ZMKLM100VB45.750	DF	100	758			3,559	1	STK
ZMKLM100VB45.800	DF	100	808			3,636	1	STK
ZMKLM100VB45.900	DF	100	908			3,790	1	STK
ZMKLM100VB45.1000	DF	100	1008			3,943	1	STK

Zu befestigen mit:



Selbstsichernde Schraube (DIN 603) RBK Verzahnte Flanschnutter (DIN 6923) RM

Min. Anzahl Schrauben und Muttern: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender