

DKLMZWVB

Deckel für leiter fallstück 90°



Zu befestigen mit:



Deckelklemme
ZMDKIG

Radius: 600 mm

| Referenz | Oberfläche | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Einheit |
|------------------------|------------|---------|---------|------------|---------|--------|---|---------|
| DKLM125VB150 | SZ | 15 | 156 | 0,9 | | 1,307 | 1 | STK |
| DKLM125VB200 | SZ | 15 | 206 | 0,9 | | 1,740 | 1 | STK |
| DKLM125VB300 | SZ | 15 | 306 | 0,9 | | 2,605 | 1 | STK |
| DKLM125VB400 | SZ | 15 | 406 | 0,9 | | 3,471 | 1 | STK |
| DKLM125VB450 | SZ | 15 | 456 | 0,9 | | 3,904 | 1 | STK |
| DKLM125VB500 | SZ | 15 | 506 | 0,9 | | 4,336 | 1 | STK |
| DKLM125VB600 | SZ | 15 | 606 | 0,9 | | 5,202 | 1 | STK |
| DKLM125VB750 | SZ | 15 | 756 | 1,25 | | 9,030 | 1 | STK |
| DKLM125VB800 | SZ | 15 | 806 | 1,25 | | 9,631 | 1 | STK |
| DKLM125VB900 | SZ | 15 | 906 | 1,25 | | 10,833 | 1 | STK |
| DKLM125VB1000 | SZ | 15 | 1006 | 1,25 | | 12,036 | 1 | STK |
| ZMDKLM125VB150 | DF | 15 | 156 | 0,9 | | 1,307 | 1 | STK |
| ZMDKLM125VB200 | DF | 15 | 206 | 0,9 | | 1,740 | 1 | STK |
| ZMDKLM125VB300 | DF | 15 | 306 | 0,9 | | 2,605 | 1 | STK |
| ZMDKLM125VB400 | DF | 15 | 406 | 0,9 | | 3,471 | 1 | STK |
| ZMDKLM125VB450 | DF | 15 | 456 | 0,9 | | 3,904 | 1 | STK |
| ZMDKLM125VB500 | DF | 15 | 506 | 0,9 | | 4,336 | 1 | STK |
| ZMDKLM125VB600 | DF | 15 | 606 | 0,9 | | 5,202 | 1 | STK |
| ZMDKLM125VB750 | DF | 15 | 756 | 1,25 | | 9,030 | 1 | STK |
| ZMDKLM125VB800 | DF | 15 | 806 | 1,25 | | 9,631 | 1 | STK |
| ZMDKLM125VB900 | DF | 15 | 906 | 1,25 | | 10,833 | 1 | STK |
| ZMDKLM125VB1000 | DF | 15 | 1006 | 1,25 | | 12,036 | 1 | STK |

Deckel für Leiterzubehör als Standardausstattung Deckel kann für die Leitern KLM100-KLM125-KLW-KLZ verwendet werden.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender