


KLM125SB45

Steigestück für KLM125



Zu befestigen mit:



Selbstsichernde
Schraube (DIN
603)
RBK

Verzahnte
Flanschmutter
(DIN 6923)
RM

Radius: 600 mm

Standardausführung

Sendzimir verzinkt

Ausführung Option

Ausführung Option PE

Polyester-Pulverbeschichtung

| HD | Referenz | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Lager | Einheit |
|----|--------------------------|---------|---------|------------|---------|--------|---|-------|---------|
| - | KLM125SB45.150 | 125 | 158 | | | 3,284 | 1 | | STK |
| - | KLM125SB45.200 | 125 | 208 | | | 3,400 | 1 | | STK |
| - | KLM125SB45.300 | 125 | 308 | | | 3,630 | 1 | | STK |
| - | KLM125SB45.400 | 125 | 408 | | | 3,860 | 1 | | STK |
| - | KLM125SB45.450 | 125 | 458 | | | 3,976 | 1 | | STK |
| - | KLM125SB45.500 | 125 | 508 | | | 4,091 | 1 | | STK |
| - | KLM125SB45.600 | 125 | 608 | | | 4,321 | 1 | | STK |
| - | KLM125SB45.750 | 125 | 758 | | | 4,667 | 1 | | STK |
| - | KLM125SB45.800 | 125 | 808 | | | 4,782 | 1 | | STK |
| - | KLM125SB45.900 | 125 | 908 | | | 5,012 | 1 | | STK |
| - | KLM125SB45.1000 | 125 | 1008 | | | 5,243 | 1 | | STK |
| - | ZMKLM125SB45.150 | 125 | 158 | | | 3,284 | 1 | | STK |
| - | ZMKLM125SB45.200 | 125 | 208 | | | 3,400 | 1 | | STK |
| - | ZMKLM125SB45.300 | 125 | 308 | | | 3,630 | 1 | | STK |
| - | ZMKLM125SB45.400 | 125 | 408 | | | 3,860 | 1 | | STK |
| - | ZMKLM125SB45.450 | 125 | 458 | | | 3,976 | 1 | | STK |
| - | ZMKLM125SB45.500 | 125 | 508 | | | 4,091 | 1 | | STK |
| - | ZMKLM125SB45.600 | 125 | 608 | | | 4,321 | 1 | | STK |
| - | ZMKLM125SB45.750 | 125 | 758 | | | 4,667 | 1 | | STK |
| - | ZMKLM125SB45.800 | 125 | 808 | | | 4,782 | 1 | | STK |
| - | ZMKLM125SB45.900 | 125 | 908 | | | 5,012 | 1 | | STK |
| - | ZMKLM125SB45.1000 | 125 | 1008 | | | 5,243 | 1 | | STK |

Min. Anzahl Schrauben und Muttern: 8 Stück.