

KLM125T

T-Stück für KLM125



Zu befestigen mit:



Selbstsichernde
Schraube (DIN
603)
RBK

Verzahnte
Flanschmutter
(DIN 6923)
RM

Radius: 600 mm

	200	300	400	500	600
A	1962	2062	2162	2262	2362

Referenz	Oberfläche	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	Einheit
KLM125T150	SZ	125	158			13,043	1 STK
KLM125T200	SZ	125	208			13,601	1 STK
KLM125T300	SZ	125	308			14,716	1 STK
KLM125T400	SZ	125	408			15,808	1 STK
KLM125T450	SZ	125	458			16,360	1 STK
KLM125T500	SZ	125	508			16,912	1 STK
KLM125T600	SZ	125	608			19,316	1 STK
KLM125T750	SZ	125	758			21,156	1 STK
KLM125T800	SZ	125	808			21,769	1 STK
KLM125T900	SZ	125	908			23,655	1 STK
KLM125T1000	SZ	125	1008			24,958	1 STK
ZMKLM125T150	DF	125	158			13,043	1 STK
ZMKLM125T200	DF	125	208			13,601	1 STK
ZMKLM125T300	DF	125	308			14,716	1 STK
ZMKLM125T400	DF	125	408			15,808	1 STK
ZMKLM125T450	DF	125	458			16,360	1 STK
ZMKLM125T500	DF	125	508			16,912	1 STK
ZMKLM125T600	DF	125	608			19,316	1 STK
ZMKLM125T750	DF	125	758			21,156	1 STK
ZMKLM125T800	DF	125	808			21,769	1 STK
ZMKLM125T900	DF	125	908			23,655	1 STK
ZMKLM125T1000	DF	125	1008			24,958	1 STK

Min. Anzahl Schrauben und Muttern: 12 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender