

KLM125VSB

Steige- und Fallstück für KLM125



In die Öffnung der Längsholme zu schieben
Vormontiert

Zu befestigen mit:



Selbstsichernde
Schraube (DIN
603)
RBK

Verzahnte
Flanschmutter
(DIN 6923)
RM

Referenz	Oberfläche	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	Einheit
KLM125VSB150	SZ	125	158		1135	10,082	1 STK
KLM125VSB200	SZ	125	208		1135	10,197	1 STK
KLM125VSB300	SZ	125	308		1135	10,428	1 STK
KLM125VSB400	SZ	125	408		1135	10,658	1 STK
KLM125VSB450	SZ	125	458		1135	10,773	1 STK
KLM125VSB500	SZ	125	508		1135	10,888	1 STK
KLM125VSB600	SZ	125	608		1135	11,119	1 STK
KLM125VSB750	SZ	125	758		1135	11,349	1 STK
KLM125VSB800	SZ	125	808		1135	11,580	1 STK
KLM125VSB900	SZ	125	908		1135	11,810	1 STK
KLM125VSB1000	SZ	125	1008		1135	12,041	1 STK
ZMKLM125VSB150	DF	125	158		1135	10,082	1 STK
ZMKLM125VSB200	DF	125	208		1135	10,197	1 STK
ZMKLM125VSB300	DF	125	308		1135	10,428	1 STK
ZMKLM125VSB400	DF	125	408		1135	10,658	1 STK
ZMKLM125VSB450	DF	125	458		1135	10,773	1 STK
ZMKLM125VSB500	DF	125	508		1135	10,888	1 STK
ZMKLM125VSB600	DF	125	608		1135	11,119	1 STK
ZMKLM125VSB750	DF	125	758		1135	11,349	1 STK
ZMKLM125VSB800	DF	125	808		1135	11,580	1 STK
ZMKLM125VSB900	DF	125	908		1135	11,810	1 STK
ZMKLM125VSB1000	DF	125	1008		1135	12,041	1 STK

Min. Anzahl Schrauben und Muttern: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender