

KLM125VSB

Steige- und Fallstück für KLM125



In die Öffnung der Längsholme zu schieben
Vormontiert

Zu befestigen mit:



Selbstsichernde
Schraube (DIN
603)
RBK

Verzahnte
Flanschmutter
(DIN 6923)
RM

| Referenz | Oberfläche | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Einheit |
|------------------------|------------|---------|---------|------------|---------|--------|---|---------|
| KLM125VSB150 | SZ | 125 | 158 | | 1135 | 10,082 | 1 | STK |
| KLM125VSB200 | SZ | 125 | 208 | | 1135 | 10,197 | 1 | STK |
| KLM125VSB300 | SZ | 125 | 308 | | 1135 | 10,428 | 1 | STK |
| KLM125VSB400 | SZ | 125 | 408 | | 1135 | 10,658 | 1 | STK |
| KLM125VSB450 | SZ | 125 | 458 | | 1135 | 10,773 | 1 | STK |
| KLM125VSB500 | SZ | 125 | 508 | | 1135 | 10,888 | 1 | STK |
| KLM125VSB600 | SZ | 125 | 608 | | 1135 | 11,119 | 1 | STK |
| KLM125VSB750 | SZ | 125 | 758 | | 1135 | 11,349 | 1 | STK |
| KLM125VSB800 | SZ | 125 | 808 | | 1135 | 11,580 | 1 | STK |
| KLM125VSB900 | SZ | 125 | 908 | | 1135 | 11,810 | 1 | STK |
| KLM125VSB1000 | SZ | 125 | 1008 | | 1135 | 12,041 | 1 | STK |
| ZMKLM125VSB150 | DF | 125 | 158 | | 1135 | 10,082 | 1 | STK |
| ZMKLM125VSB200 | DF | 125 | 208 | | 1135 | 10,197 | 1 | STK |
| ZMKLM125VSB300 | DF | 125 | 308 | | 1135 | 10,428 | 1 | STK |
| ZMKLM125VSB400 | DF | 125 | 408 | | 1135 | 10,658 | 1 | STK |
| ZMKLM125VSB450 | DF | 125 | 458 | | 1135 | 10,773 | 1 | STK |
| ZMKLM125VSB500 | DF | 125 | 508 | | 1135 | 10,888 | 1 | STK |
| ZMKLM125VSB600 | DF | 125 | 608 | | 1135 | 11,119 | 1 | STK |
| ZMKLM125VSB750 | DF | 125 | 758 | | 1135 | 11,349 | 1 | STK |
| ZMKLM125VSB800 | DF | 125 | 808 | | 1135 | 11,580 | 1 | STK |
| ZMKLM125VSB900 | DF | 125 | 908 | | 1135 | 11,810 | 1 | STK |
| ZMKLM125VSB1000 | DF | 125 | 1008 | | 1135 | 12,041 | 1 | STK |

Min. Anzahl Schrauben und Muttern: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender