


KLWVB

Fallstück für KLV



Zu befestigen mit:



Verzahnte
Flanschmutter
(DIN 6923)
RM

Selbstsichernde
Schraube (DIN
603)
RBK

| Radius: 600 mm | | | | | | | | | |
|----------------------|-------------------|---------|---------|--------------------|------------------------------|--------|---|-------|---------|
| Standardausführung | | | | Sendzimir verzinkt | | | | | |
| Ausführung Option | | | | | | | | | |
| Ausführung Option PE | | | | | Polyester-Pulverbeschichtung | | | | |
| HD | Referenz | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Lager | Einheit |
| - | KLWVB200 | 200 | 208 | | | 7,795 | 1 | | STK |
| - | KLWVB300 | 200 | 308 | | | 8,026 | 1 | | STK |
| - | KLWVB400 | 200 | 408 | | | 8,256 | 1 | | STK |
| - | KLWVB500 | 200 | 508 | | | 8,487 | 1 | | STK |
| - | KLWVB600 | 200 | 608 | | | 8,717 | 1 | | STK |
| - | ZMKLWVB200 | 200 | 208 | | | 7,795 | 1 | | STK |
| - | ZMKLWVB300 | 200 | 308 | | | 8,026 | 1 | | STK |
| - | ZMKLWVB400 | 200 | 408 | | | 8,256 | 1 | | STK |
| - | ZMKLWVB500 | 200 | 508 | | | 8,487 | 1 | | STK |
| - | ZMKLWVB600 | 200 | 608 | | | 8,717 | 1 | | STK |

Min. Anzahl Schrauben und Muttern: 8 Stück.