

# CS45SHY

## Kabelaufhängung Y-split mit Haken



Max. Belastung: 45 daN

Standardausführung

Sendzimir verzinkt

| HD | Referenz           | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦  | Lager | Einheit |
|----|--------------------|---------|---------|------------|---------|--------|----|-------|---------|
| -  | <b>CS45SH150Y1</b> |         | 150     |            | 1000    | 0,100  | 10 |       | STK     |
| -  | <b>CS45SH150Y2</b> |         | 150     |            | 2000    | 0,100  | 10 |       | STK     |
| -  | <b>CS45SH150Y3</b> |         | 150     |            | 3000    | 0,100  | 10 |       | STK     |
| -  | <b>CS45SH300Y1</b> |         | 300     |            | 1000    | 0,150  | 10 |       | STK     |
| -  | <b>CS45SH300Y2</b> |         | 300     |            | 2000    | 0,150  | 10 |       | STK     |
| -  | <b>CS45SH300Y3</b> |         | 300     |            | 3000    | 0,150  | 10 |       | STK     |
| -  | <b>CS45SH500Y1</b> |         | 500     |            | 1000    | 0,250  | 10 |       | STK     |
| -  | <b>CS45SH500Y2</b> |         | 500     |            | 2000    | 0,250  | 10 |       | STK     |
| -  | <b>CS45SH500Y3</b> |         | 500     |            | 3000    | 0,250  | 10 |       | STK     |
| -  | <b>CS45SH800Y1</b> |         | 800     |            | 1000    | 0,400  | 10 |       | STK     |
| -  | <b>CS45SH800Y2</b> |         | 800     |            | 2000    | 0,400  | 10 |       | STK     |
| -  | <b>CS45SH800Y3</b> |         | 800     |            | 3000    | 0,400  | 10 |       | STK     |

Abgabe nur in vollen Verpackungseinheiten.