

I6KLM100.3

Cable ladder height 100



Cable ladder for large support distances up to 8 metres
Perforated C rungs 41 x 21

Usable inner height: 102 mm
Rung distance: 250 mm
To order: Length 3000 mm

Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/m	📦	Unit
I6KLM100.150.3	100	150		3000	5,135	3	M
I6KLM100.200.3	100	200		3000	5,263	3	M
I6KLM100.300.3	100	300		3000	5,519	3	M
I6KLM100.400.3	100	400		3000	5,775	3	M
I6KLM100.450.3	100	450		3000	5,903	3	M
I6KLM100.500.3	100	500		3000	6,031	3	M
I6KLM100.600.3	100	600		3000	6,287	3	M
I6KLM100.750.3	100	750		3000	6,671	3	M
I6KLM100.800.3	100	800		3000	6,799	3	M
I6KLM100.900.3	100	900		3000	7,055	3	M
I6KLM100.1000.3	100	1000		3000	7,311	3	M

CHARACTERISTICS

- strong
- usable inner height 102 mm, ideal for large diameter cables
- no further coupling holes are required if the cable ladder is cut
- no joiners are required to attach accessories such as bends, tees etc.
- rungs are perforated to enable efficient attachment of cables
- partition (I6SLOS60) can be fixed to the cable ladder with a sliding nut (I6PNP06) and pan head bolt (I6RB6.20).

TECHNICAL INFORMATION

- Side walls are constructed from S profile with a return flange and are continuously perforated
- C-profile rungs are fixed at 250 mm intervals.
 - rungs are mechanically attached to the side wall of the cable ladder.
 - rungs are alternately placed with openings upwards and downwards.

Pickled and passivated.