


I6KLM125B45

Horizontal bend for I6KLM125



Fix with:



Round head
square neck bolt
(DIN 603)
RBK

Flange nut (DIN
6923)
RM

Radius: 600 mm

Standard finish

Stainless Steel 316

| HD | Reference | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Stock | Unit |
|----|-------------------------|---------|---------|------------|---------|--------|---|-------|------|
| - | I6KLM125B45.150 | 125 | 150 | | | 4,187 | 1 | | STK |
| - | I6KLM125B45.200 | 125 | 200 | | | 4,421 | 1 | | STK |
| - | I6KLM125B45.300 | 125 | 300 | | | 4,888 | 1 | | STK |
| - | I6KLM125B45.400 | 125 | 400 | | | 5,355 | 1 | | STK |
| - | I6KLM125B45.450 | 125 | 450 | | | 5,589 | 1 | | STK |
| - | I6KLM125B45.500 | 125 | 500 | | | 6,188 | 1 | | STK |
| - | I6KLM125B45.600 | 125 | 600 | | | 6,733 | 1 | | STK |
| - | I6KLM125B45.750 | 125 | 750 | | | 7,552 | 1 | | STK |
| - | I6KLM125B45.800 | 125 | 800 | | | 7,825 | 1 | | STK |
| - | I6KLM125B45.900 | 125 | 900 | | | 8,372 | 1 | | STK |
| - | I6KLM125B45.1000 | 125 | 1000 | | | 9,677 | 1 | | STK |

Minimum number bolts and nuts: 8 pieces.