


# KLLSB

## Internal riser for KLL



Fix with:



Toothed round head bolt / flange nut  
VM

Radius: 300 mm

Standard finish

Pre-galvanised

Optional finish

Hot-dip galvanised

Optional finish PE

Coating

HD	Reference	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Stock	Unit
HD	<b>KLLSB60.150</b>	60	146			1,528	1		STK
HD	<b>KLLSB60.200</b>	60	196			1,629	1		STK
HD	<b>KLLSB60.300</b>	60	296			1,830	1		STK
HD	<b>KLLSB60.400</b>	60	396			2,032	1		STK
HD	<b>KLLSB60.450</b>	60	443			2,133	1		STK
HD	<b>KLLSB60.500</b>	60	496			2,234	1		STK
HD	<b>KLLSB60.600</b>	60	596			2,435	1		STK
HD	<b>KLLSB85.150</b>	85	145			1,922	1		STK
HD	<b>KLLSB85.200</b>	85	196			2,083	1		STK
HD	<b>KLLSB85.300</b>	85	296			2,284	1		STK
HD	<b>KLLSB85.400</b>	85	396			2,486	1		STK
HD	<b>KLLSB85.450</b>	85	445			2,587	1		STK
HD	<b>KLLSB85.500</b>	85	496			2,688	1		STK
HD	<b>KLLSB85.600</b>	85	596			2,889	1		STK

Minimum number bolts and nuts VM6.10: 8 pieces.