


KLLX


Cross-over for KLL



Radius: 300 mm	
Standard finish	Pre-galvanised
Optional finish	Hot-dip galvanised
Optional finish PE	Coating

	150	200	300	400	500	600
A	1021	1071	1171	1271	1371	1471

Fix with:



Toothed round head bolt / flange nut
VM

HD	Reference	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit
HD	KLLX60.150	60	141			3,131	1		STK
HD	KLLX60.200	60	191			3,232	1		STK
HD	KLLX60.300	60	291			4,421	1		STK
HD	KLLX60.400	60	391			4,875	1		STK
HD	KLLX60.450	60	443			5,102	1		STK
HD	KLLX60.500	60	491			5,329	1		STK
HD	KLLX60.600	60	591			5,782	1		STK
HD	KLLX85.150	85	145			3,525	1		STK
HD	KLLX85.200	85	195			4,032	1		STK
HD	KLLX85.300	85	295			5,221	1		STK
HD	KLLX85.400	85	395			5,675	1		STK
HD	KLLX85.450	85	445			5,902	1		STK
HD	KLLX85.500	85	495			6,129	1		STK
HD	KLLX85.600	85	595			6,582	1		STK

Minimum number bolts and nuts VM6.10: 16 pieces.