


KLM125SB45

Internal riser for KLM125



Radius: 600 mm

Standard finish

Pre-galvanised

Optional finish

Optional finish PE

Coating

HD	Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit
-	KLM125SB45.150	125	158			3,284	1		STK
-	KLM125SB45.200	125	208			3,400	1		STK
-	KLM125SB45.300	125	308			3,630	1		STK
-	KLM125SB45.400	125	408			3,860	1		STK
-	KLM125SB45.450	125	458			3,976	1		STK
-	KLM125SB45.500	125	508			4,091	1		STK
-	KLM125SB45.600	125	608			4,321	1		STK
-	KLM125SB45.750	125	758			4,667	1		STK
-	KLM125SB45.800	125	808			4,782	1		STK
-	KLM125SB45.900	125	908			5,012	1		STK
-	KLM125SB45.1000	125	1008			5,243	1		STK
-	ZMKLM125SB45.150	125	158			3,284	1		STK
-	ZMKLM125SB45.200	125	208			3,400	1		STK
-	ZMKLM125SB45.300	125	308			3,630	1		STK
-	ZMKLM125SB45.400	125	408			3,860	1		STK
-	ZMKLM125SB45.450	125	458			3,976	1		STK
-	ZMKLM125SB45.500	125	508			4,091	1		STK
-	ZMKLM125SB45.600	125	608			4,321	1		STK
-	ZMKLM125SB45.750	125	758			4,667	1		STK
-	ZMKLM125SB45.800	125	808			4,782	1		STK
-	ZMKLM125SB45.900	125	908			5,012	1		STK
-	ZMKLM125SB45.1000	125	1008			5,243	1		STK

Fix with:



Round head
square neck bolt
(DIN 603)
RBK

Flange nut (DIN
6923)
RM

Minimum number bolts and nuts: 8 pieces.