

KLWSB

Internal riser for KLW



Fix with:



Round head
square neck bolt
(DIN 603)
RBK

Flange nut (DIN
6923)
RM

Radius: 600 mm

| Reference | Finish | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|-------------------|--------|---------|---------|------------|---------|--------|---|------|
| KLWSB200 | SZ | 200 | 208 | | | 7,921 | 1 | STK |
| KLWSB300 | SZ | 200 | 308 | | | 8,228 | 1 | STK |
| KLWSB400 | SZ | 200 | 408 | | | 8,535 | 1 | STK |
| KLWSB500 | SZ | 200 | 508 | | | 8,842 | 1 | STK |
| KLWSB600 | SZ | 200 | 608 | | | 9,149 | 1 | STK |
| ZMKLWSB200 | DF | 200 | 208 | | | 7,921 | 1 | STK |
| ZMKLWSB300 | DF | 200 | 308 | | | 8,228 | 1 | STK |
| ZMKLWSB400 | DF | 200 | 408 | | | 8,535 | 1 | STK |
| ZMKLWSB500 | DF | 200 | 508 | | | 8,842 | 1 | STK |
| ZMKLWSB600 | DF | 200 | 608 | | | 9,149 | 1 | STK |

Minimum number bolts and nuts: 8 pieces.

Legend finish
- SZ = Sendzimir
- DF = Defender