

# TALON®

## Cable Cleat 41" 21 mm for KLM100 - KLM125 - K LW - KLZ



TALON® cable cleats provide support, restraint, strain relief, and protect cable management systems during a short-circuit by containing the cables without damage. With a full range of frame sizes, TALON® cable cleats can accommodate cables with outer diameters ranging from 13 mm to 108 mm.

Reference	↕ mm	↔ mm	→  ← mm	↔↔ mm	kg/stk	📦	Unit
<b>T306-F1H4R00-00</b>	193,6	197,4		110,0	0,51	36	STK
<b>T305-F1H4R00-00</b>	168,9	168,4		110,0	0,64	18	STK
<b>T304-F1H4R00-00</b>	148,9	147,8		110,0	0,64	18	STK
<b>T303-F1H4R00-00</b>	132,9	130,5		110,0	0,51	36	STK
<b>T106-F1H4R00-00</b>	167,0	156,2		110,0	0,64	18	STK
<b>T105-F1H4R00-00</b>	140,0	126,7		110,0	0,79	18	STK
<b>T104-F1H4R00-00</b>	110,0	110,0		101,6	0,79	18	STK
<b>MT KIT H4_3/8X2</b>	50,0	100,0		100,0	0,20	1	STK

Works with Unistrut profile width 41 mm. For assembly on Strut: also order 2 pc MT KIT H4\_3/8X2 per cleat for T104,T105,106,107,T 304,T305 For assembly on Strut: also order 1 pc MT KIT H4\_3/8X2 for T303

They are packed per 2 pieces. Not to be used on ladder with floorplate.