


KLZVSB

Flexible (rising / low) bend for KLZ



Fix with:



Round head square neck bolt (DIN 603) RBK

Flange nut (DIN 6923) RM

| Reference | Finish | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|--------------------|--------|---------|---------|--------------|---------|--------|---|------|
| KLZVSB200 | - | 150 | 218 | | 1135 | 13,680 | 1 | STK |
| KLZVSB300 | - | 150 | 318 | | 1135 | 14,000 | 1 | STK |
| KLZVSB400 | - | 150 | 418 | | 1135 | 14,320 | 1 | STK |
| KLZVSB500 | - | 150 | 518 | | 1135 | 14,640 | 1 | STK |
| KLZVSB600 | - | 150 | 618 | | 1135 | 14,964 | 1 | STK |
| HDKLZVSB200 | HD | 150 | 200 | 2,0/1,25/3,0 | 1135 | 13,680 | 1 | STK |
| HDKLZVSB300 | HD | 150 | 300 | 2,0/1,25/3,0 | 1135 | 14,000 | 1 | STK |
| HDKLZVSB400 | HD | 150 | 400 | 2,0/1,25/3,0 | 1135 | 14,320 | 1 | STK |
| HDKLZVSB500 | HD | 150 | 500 | 2,0/1,25/3,0 | 1135 | 14,640 | 1 | STK |
| HDKLZVSB600 | HD | 150 | 600 | 2,0/1,25/3,0 | 1135 | 14,964 | 1 | STK |

Minimum number bolts and nuts: 8 pieces.

Legend finish

- HD =