

# AS

## Horizontal adapter 90°



Slides over the cable trays

Radius: 100 mm

To order: Height 35 mm - 85 mm - 110 mm (only in SZ and HD)


	50	75	100	150	200	300	400	500	600
A	458	483	508	558	608	708	808	908	1008

Reference	Finish	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unit
<b>ZMAS110.100</b>	DF	110	100	0,75		0,691	1	STK
<b>ZMAS110.150</b>	DF	110	150	0,75		0,757	1	STK
<b>ZMAS110.200</b>	DF	110	200	0,75		0,821	1	STK
<b>ZMAS110.300</b>	DF	110	300	0,75		0,944	1	STK
<b>ZMAS110.400</b>	DF	110	400	0,75		1,075	1	STK
<b>ZMAS110.500</b>	DF	110	500	0,75/0,9		1,407	1	STK
<b>ZMAS110.600</b>	DF	110	600	0,75/0,9		1,576	1	STK
<b>ZMAS85.100</b>	DF	85	100	0,75		0,600	1	STK
<b>ZMAS85.150</b>	DF	85	150	0,75		0,666	1	STK
<b>ZMAS85.200</b>	DF	85	200	0,75		0,730	1	STK
<b>ZMAS85.300</b>	DF	85	300	0,75		0,853	1	STK
<b>ZMAS85.400</b>	DF	85	400	0,75		0,984	1	STK
<b>ZMAS85.500</b>	DF	85	500	0,75/0,9		1,316	1	STK
<b>ZMAS85.600</b>	DF	85	600	0,75/0,9		1,486	1	STK
<b>ZMAS60.100</b>	DF	60	100			0,512	1	STK
<b>ZMAS60.050</b>	DF	60	50			0,446	1	STK
<b>ZMAS60.075</b>	DF	60	75			0,479	1	STK
<b>ZMAS60.150</b>	DF	60	150			0,578	1	STK
<b>ZMAS60.200</b>	DF	60	200			0,642	1	STK
<b>ZMAS60.300</b>	DF	60	300			0,765	1	STK
<b>ZMAS60.400</b>	DF	60	400			0,896	1	STK
<b>ZMAS60.500</b>	DF	60	500			1,228	1	STK
<b>ZMAS60.600</b>	DF	60	600			1,398	1	STK

### Fix with:



Toothed round head bolt / flange nut  
VM



Round head square neck bolt / flange nut  
VMK

Minimum number bolts and nuts: 8 pieces.

### Legend finish

- DF = Defender

