


T

Horizontal T-piece



Slides over the cable trays

Radius: 100 mm

To order: Height 35 mm - 85 mm - 110 mm

| | | | | | | | | | |
|---|-----|-----|-----|-----|-----|-----|-----|-----|------|
| | 50 | 75 | 100 | 150 | 200 | 300 | 400 | 500 | 600 |
| A | 458 | 483 | 508 | 558 | 608 | 708 | 808 | 908 | 1008 |

Fix with:



Toothed round head bolt / flange nut
VM



Round head square neck bolt / flange nut
VMK

| Reference | Finish | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|-------------------|--------|---------|---------|------------|---------|--------|---|------|
| ZMT110.100 | DF | 110 | 100 | 0,75 | | 1,265 | 1 | STK |
| ZMT110.150 | DF | 110 | 150 | 0,75 | | 1,538 | 1 | STK |
| ZMT110.200 | DF | 110 | 200 | 0,75 | | 1,838 | 1 | STK |
| ZMT110.300 | DF | 110 | 300 | 0,75 | | 2,522 | 1 | STK |
| ZMT110.400 | DF | 110 | 400 | 0,75 | | 3,315 | 1 | STK |
| ZMT110.500 | DF | 110 | 500 | 0,75/0,9 | | 5,098 | 1 | STK |
| ZMT110.600 | DF | 110 | 600 | 0,75/0,9 | | 6,380 | 1 | STK |
| ZMT85.100 | DF | 85 | 100 | 0,75 | | 1,108 | 1 | STK |
| ZMT85.150 | DF | 85 | 150 | 0,75 | | 1,374 | 1 | STK |
| ZMT85.200 | DF | 85 | 200 | 0,75 | | 1,668 | 1 | STK |
| ZMT85.300 | DF | 85 | 300 | 0,75 | | 2,338 | 1 | STK |
| ZMT85.400 | DF | 85 | 400 | 0,75 | | 3,117 | 1 | STK |
| ZMT85.500 | DF | 85 | 500 | 0,75/0,9 | | 4,887 | 1 | STK |
| ZMT85.600 | DF | 85 | 600 | 0,75/0,9 | | 6,155 | 1 | STK |
| ZMT60.050 | DF | 60 | 50 | | | 0,722 | 1 | STK |
| ZMT60.075 | DF | 60 | 75 | | | 0,835 | 1 | STK |
| ZMT60.100 | DF | 60 | 100 | | | 0,954 | 1 | STK |
| ZMT60.150 | DF | 60 | 150 | | | 1,213 | 1 | STK |
| ZMT60.200 | DF | 60 | 200 | | | 1,500 | 1 | STK |
| ZMT60.300 | DF | 60 | 300 | | | 2,156 | 1 | STK |
| ZMT60.400 | DF | 60 | 400 | | | 2,922 | 1 | STK |
| ZMT60.500 | DF | 60 | 500 | | | 4,678 | 1 | STK |
| ZMT60.600 | DF | 60 | 600 | | | 5,932 | 1 | STK |

Minimum number bolts and nuts: 12 pieces.

Legend finish

- DF = Defender