

# VS

## Reducing plate



To order: Height 35 mm - 85 mm - 110 mm (just SZ and HD)

Reference	Finish	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unit
ZMVS110.025	DF	110	25	0,75	200	0,108	1	STK
ZMVS110.050	DF	110	50	0,75	200	0,121	1	STK
ZMVS110.075	DF	110	75	0,75	200	0,135	1	STK
ZMVS110.100	DF	110	100	0,75	200	0,149	1	STK
ZMVS110.125	DF	110	125	0,75	200	0,163	1	STK
ZMVS110.150	DF	110	150	0,75	200	0,176	1	STK
ZMVS110.200	DF	110	200	0,75	200	0,204	1	STK
ZMVS110.250	DF	110	250	0,75	200	0,231	1	STK
ZMVS110.300	DF	110	300	0,75	200	0,259	1	STK
ZMVS110.350	DF	110	350	0,75	200	0,286	1	STK
ZMVS110.400	DF	110	400	0,75	200	0,314	1	STK
ZMVS85.025	DF	85	25	0,75	200	0,081	1	STK
ZMVS85.050	DF	85	50	0,75	200	0,091	1	STK
ZMVS85.075	DF	85	75	0,75	200	0,101	1	STK
ZMVS85.100	DF	85	100	0,75	200	0,112	1	STK
ZMVS85.125	DF	85	125	0,75	200	0,122	1	STK
ZMVS85.150	DF	85	150	0,75	200	0,132	1	STK
ZMVS85.200	DF	85	200	0,75	200	0,153	1	STK
ZMVS85.250	DF	85	250	0,75	200	0,173	1	STK
ZMVS85.300	DF	85	300	0,75	200	0,194	1	STK
ZMVS85.350	DF	85	350	0,75	200	0,215	1	STK
ZMVS85.400	DF	85	400	0,75	200	0,235	1	STK
ZMVS60.025	DF	50	25			0,088	1	STK
ZMVS60.050	DF	50	50			0,088	1	STK
ZMVS60.075	DF	50	75			0,099	1	STK
ZMVS60.100	DF	50	100			0,110	1	STK
ZMVS60.125	DF	50	125			0,110	1	STK
ZMVS60.150	DF	50	150			0,121	1	STK
ZMVS60.200	DF	50	200			0,132	1	STK
ZMVS60.250	DF	50	250			0,154	1	STK
ZMVS60.300	DF	50	300			0,198	1	STK
ZMVS60.350	DF	50	350			0,198	1	STK
ZMVS60.400	DF	50	400			0,231	1	STK

### Fix with:



Toothed round head bolt / flange nut  
VM



Round head square neck bolt / flange nut  
VMK

Minimum number bolts and nuts: 4 pieces.

### Legend finish

- DF = Defender

