

KBSM(I)60

Cable tray machine constr. interl. ends




Can be used with RBKBSM
Alternative perforation
Return flanges

| Reference | ↔ mm | ↔ mm | → ← mm | ↔ mm | kg/m | Unit |
|------------------------|------|------|---------|------|-------|------|
| KBSM60.050.100 | 60 | 50 | 1 | 3000 | 1,240 | 3 M |
| KBSMI60.075.100 | 60 | 75 | 1 | 3000 | 1,400 | 3 M |

LOAD DIAGRAM

This diagram illustrates the permissible uniformly distributed loads applied to multiple supports. They comply with IEC 61537 par 10.3.3 test type III with connection to 1/5 of the span.



Fix with:



Toothed round head bolt / flange nut
VM

F = max. admissible load (daN/m)

L = support distance (m)

Max. deflection (m) = L/100

CHARACTERISTICS

- The cable outlet holes allow the cable trays to be used in machine constructions, especially in the field of internal transport. The KBSMI cable trays can also be combined with KBSI and KGI.
- Can be used as lighting rail by immediately connecting through bottom perforations M16 and M20.
- Staggered slots in sides and bottom for easy connection with accessories.
- To be used with standard accessories, such as the cover with swivel clamp.
- Only DCO to be used with cover.

TECHNICAL INFORMATION

- Interlocking from width 75 mm (connect width 50 mm with joining plate)
- Large cable outlet with round corners (dimensions 30x50 mm)
- Distance between cable outlets: bottom = 150 mm, sides = 300 mm
- Edge protection RBKBSM to order separately
- Round cable gland central to the bottom, alternately M16/M20