



# KDRKK3

## Hinged cover round, universal



Build-in frame + hinged cover + cable outlet unit

Color: Grey RAL 7011/ Black RAL 9011  
 Max. load: 1500 N (small surface area)  
 Max. load: 2000 N (large surface area)  
 Active condition: IP 20  
 Non-active condition: IP 30  
 Depth of floor covering: Min. 5 mm - Max. 12 mm  
 Thickness steel plate : 3 mm

| Standard finish |                      | Polypropylene |         |            |         |        |   |       |      |
|-----------------|----------------------|---------------|---------|------------|---------|--------|---|-------|------|
| HD              | Reference            | ↕<br>mm       | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Stock | Unit |
| -               | <b>KDRKK3.5-7011</b> |               | 327     |            | 327     | 2,450  | 6 | X     | STK  |
| -               | <b>KDRKK3.5-9011</b> |               | 327     |            | 327     | 2,450  | 6 | X     | STK  |

Tested to EN 50085-2-2.

Hinged cover for 3 compartments.

Standard depth of floor covering is 5 mm and can be reduced by fitting packers OHER3.2 and/or OHER3.5.

Replace the clamps of the hinged cover by the enclosed clamps of the DOVG.

Hinged cover is provided with 2 cable outlets with integrated push lever and cable organiser.

Hinged cover must not be earthed.

For use in dry floors only.