

COMEGACLU290

Open suspension bracket universal



Useful for direct mounting to the ceiling or with threaded rod TIM8 or TIM10.

| | |
|--------------------|--------------------|
| Standard finish | Pre-galvanised |
| Optional finish | Hot-dip galvanised |
| Optional finish PE | Coating |

| | Max. load (in daN) | A |
|------------------|--------------------|-----|
| COMEGACLU290.100 | 70 | 145 |
| COMEGACLU290.150 | 60 | 145 |
| COMEGACLU290.200 | 60 | 145 |
| COMEGACLU290.250 | 50 | 195 |
| COMEGACLU290.300 | 50 | 195 |
| COMEGACLU290.400 | 40 | 245 |

| HD | Reference | ↑↓ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Stock | Unit |
|----|-------------------------|----------|---------|------------|---------|--------|----|-------|------|
| HD | COMEGACLU290.100 | 290 | 145 | | | 0,520 | 12 | X | STK |
| HD | COMEGACLU290.150 | 290 | 194 | | | 0,560 | 12 | X | STK |
| HD | COMEGACLU290.200 | 290 | 244 | | | 0,620 | 12 | X | STK |
| HD | COMEGACLU290.250 | 290 | 294 | | | 0,760 | 6 | X | STK |
| HD | COMEGACLU290.300 | 290 | 344 | | | 0,820 | 6 | X | STK |
| HD | COMEGACLU290.400 | 290 | 444 | | | 0,930 | 6 | X | STK |

To order per full packaging.

Fixing of the cable tray by VM6.20.

Use the VOMEGA to avoid compression of the profile.

Max. load (in daN): uniformly distributed over complete width of cantilever brackets.

Do not use with: VFUL30.065, VFUL35.150, VFU35.150, VFUL 60.050.