

# HDHSLDCL

## Double ceiling profile



Ceiling profile: HDMP41.21  
Welded headplate: 135x135 mm

Max. load: 1800 daN  
Thickness head plate: 4 mm

Standard finish Hot-dip galvanised

Optional finish PE Duplex system

HD	Reference	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Stock	Unit
-	<b>HDHSLDCL200</b>	210	21			1,000	20	X	STK
-	<b>HDHSLDCL300</b>	300	21			1,230	1	X	STK
-	<b>HDHSLDCL400</b>	420	21			1,480	1	X	STK
-	<b>HDHSLDCL500</b>	510	21			1,700	1	X	STK
-	<b>HDHSLDCL600</b>	600	21			1,900	1	X	STK
-	<b>HDHSLDCL800</b>	810	21			2,250	1	X	STK
-	<b>HDHSLDCL1000</b>	1020	21			2,900	1	X	STK
-	<b>HDHSLDCL1200</b>	1200	21			3,340	1	X	STK

For single and double sided fixing of brackets WKS, WKML and HDWK.  
Use sliding nut PNP10 and hexagonal bolt B10.20.  
Protection cap in yellow PVC: DOP41.41.

