

HSMES

Single ceiling profile



Ceiling profile: MP41.41S
Welded headplate: 135x135 mm

Max. load: 1800 daN

Reference	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Unit
HSMES200	200	41			1,020	20	STK
HSMES300	300	41			1,280	1	STK
HSMES400	400	41			1,530	1	STK
HSMES500	500	41			1,790	1	STK
HSMES600	600	41			2,050	1	STK
HSMES800	800	41			2,570	1	STK
HSMES1000	1000	41			3,090	1	STK
HSMES1200	1200	41			3,600	1	STK
HSMES1500	1500	41			4,380	1	STK
HDHSMES200	200	41			1,020	20	STK
HDHSMES300	300	41			1,280	1	STK
HDHSMES400	400	41			1,530	1	STK
HDHSMES500	500	41			1,790	1	STK
HDHSMES600	600	41			2,050	1	STK
HDHSMES800	800	41			2,570	1	STK
HDHSMES1000	1000	41			3,090	1	STK
HDHSMES1200	1200	41			3,600	1	STK
HDHSMES1500	1500	41			4,380	1	STK

Also applicable for double mounting.
Use sliding nut PNP10 and hexagonal bolt B10.30.
Protection cap in yellow PVC: DOP41.41.



