

# HSMES

## Single ceiling profile



Ceiling profile: MP41.41S  
Welded headplate: 135x135 mm

Max. load: 1800 daN

Reference	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unit
<b>HSMES200</b>	200	41			1,020	20	STK
<b>HSMES300</b>	300	41			1,280	1	STK
<b>HSMES400</b>	400	41			1,530	1	STK
<b>HSMES500</b>	500	41			1,790	1	STK
<b>HSMES600</b>	600	41			2,050	1	STK
<b>HSMES800</b>	800	41			2,570	1	STK
<b>HSMES1000</b>	1000	41			3,090	1	STK
<b>HSMES1200</b>	1200	41			3,600	1	STK
<b>HSMES1500</b>	1500	41			4,380	1	STK
<b>HDHSMES200</b>	200	41			1,020	20	STK
<b>HDHSMES300</b>	300	41			1,280	1	STK
<b>HDHSMES400</b>	400	41			1,530	1	STK
<b>HDHSMES500</b>	500	41			1,790	1	STK
<b>HDHSMES600</b>	600	41			2,050	1	STK
<b>HDHSMES800</b>	800	41			2,570	1	STK
<b>HDHSMES1000</b>	1000	41			3,090	1	STK
<b>HDHSMES1200</b>	1200	41			3,600	1	STK
<b>HDHSMES1500</b>	1500	41			4,380	1	STK

Also applicable for double mounting.  
Use sliding nut PNP10 and hexagonal bolt B10.30.  
Protection cap in yellow PVC: DOP41.41.



