


# I6KLLX

## Cross-over for I6KLL




Radius: 300 mm

|   |      |      |      |      |      |      |
|---|------|------|------|------|------|------|
|   | 150  | 200  | 300  | 400  | 500  | 600  |
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

| Reference           | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Unit |
|---------------------|---------|---------|------------|---------|--------|---|------|
| <b>I6KLLX60.150</b> | 60      | 141     |            |         | 3,879  | 1 | STK  |
| <b>I6KLLX60.200</b> | 60      | 191     |            |         | 4,112  | 1 | STK  |
| <b>I6KLLX60.300</b> | 60      | 291     |            |         | 4,710  | 1 | STK  |
| <b>I6KLLX60.400</b> | 60      | 391     |            |         | 5,224  | 1 | STK  |
| <b>I6KLLX60.500</b> | 60      | 491     |            |         | 5,966  | 1 | STK  |
| <b>I6KLLX60.600</b> | 60      | 591     |            |         | 6,527  | 1 | STK  |

### Fix with:



Toothed round head bolt / flange nut  
I6VM

Minimum number bolts and nuts: 16 pieces.

Pickled and passivated.