


I6KLM100SB45

Internal riser 45° for I6KLM100



Radius: 600 mm

| Reference | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|--------------------------|---------|---------|------------|---------|--------|---|------|
| I6KLM100SB45.150 | 100 | 150 | | | 2,793 | 1 | STK |
| I6KLM100SB45.200 | 100 | 200 | | | 2,912 | 1 | STK |
| I6KLM100SB45.300 | 100 | 300 | | | 3,148 | 1 | STK |
| I6KLM100SB45.400 | 100 | 400 | | | 3,384 | 1 | STK |
| I6KLM100SB45.450 | 100 | 450 | | | 3,502 | 1 | STK |
| I6KLM100SB45.500 | 100 | 500 | | | 3,620 | 1 | STK |
| I6KLM100SB45.600 | 100 | 600 | | | 3,856 | 1 | STK |
| I6KLM100SB45.750 | 100 | 750 | | | 4,211 | 1 | STK |
| I6KLM100SB45.800 | 100 | 800 | | | 4,329 | 1 | STK |
| I6KLM100SB45.900 | 100 | 900 | | | 4,566 | 1 | STK |
| I6KLM100SB45.1000 | 100 | 1000 | | | 4,802 | 1 | STK |

Fix with:



Round head
square neck bolt
(DIN 603)
RBK

Flange nut (DIN
6923)
RM

Minimum number bolts and nuts: 8 pieces.