


# I6KLM100VB45

## External riser 45° for I6KLM100



Radius: 600 mm

| Reference                | ↑<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Unit |
|--------------------------|---------|---------|------------|---------|--------|---|------|
| <b>I6KLM100VB45.150</b>  | 100     | 150     |            |         | 2,704  | 1 | STK  |
| <b>I6KLM100VB45.200</b>  | 100     | 200     |            |         | 2,783  | 1 | STK  |
| <b>I6KLM100VB45.300</b>  | 100     | 300     |            |         | 2,941  | 1 | STK  |
| <b>I6KLM100VB45.400</b>  | 100     | 400     |            |         | 3,097  | 1 | STK  |
| <b>I6KLM100VB45.450</b>  | 100     | 450     |            |         | 3,176  | 1 | STK  |
| <b>I6KLM100VB45.500</b>  | 100     | 500     |            |         | 3,255  | 1 | STK  |
| <b>I6KLM100VB45.600</b>  | 100     | 600     |            |         | 3,413  | 1 | STK  |
| <b>I6KLM100VB45.750</b>  | 100     | 750     |            |         | 3,649  | 1 | STK  |
| <b>I6KLM100VB45.800</b>  | 100     | 800     |            |         | 3,728  | 1 | STK  |
| <b>I6KLM100VB45.900</b>  | 100     | 900     |            |         | 3,886  | 1 | STK  |
| <b>I6KLM100VB45.1000</b> | 100     | 1000    |            |         | 4,043  | 1 | STK  |

**Fix with:**



Round head  
square neck bolt  
(DIN 603)  
RBK

Flange nut (DIN  
6923)  
RM

Minimum number bolts and nuts: 8 pieces.