


# I6KLM125SB

## Internal riser for I6KLM125



Radius: 600 mm

Reference	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unit
<b>I6KLM125SB150</b>	125	150			5,189	1	STK
<b>I6KLM125SB200</b>	125	208			5,347	1	STK
<b>I6KLM125SB300</b>	125	308			5,662	1	STK
<b>I6KLM125SB400</b>	125	408			5,977	1	STK
<b>I6KLM125SB450</b>	125	450			6,134	1	STK
<b>I6KLM125SB500</b>	125	508			6,291	1	STK
<b>I6KLM125SB600</b>	125	608			6,606	1	STK
<b>I6KLM125SB750</b>	125	750			7,079	1	STK
<b>I6KLM125SB800</b>	125	800			7,237	1	STK
<b>I6KLM125SB900</b>	125	900			7,551	1	STK
<b>I6KLM125SB1000</b>	125	000			7,866	1	STK

### Fix with:



Round head  
square neck bolt  
(DIN 603)  
I6RBK

Nut (DIN 934)  
I6M

Minimum number bolts and nuts: 8 pieces.

Pickled and passivated.



Giant washer  
(DIN 125-1 A)  
I6RO