

I6KLM125VB

External riser for I6KLM125



Radius: 600 mm

| Reference | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|-----------------------|---------|---------|------------|---------|--------|---|------|
| I6KLM125VB150 | 125 | 150 | | | 5,100 | 1 | STK |
| I6KLM125VB200 | 125 | 208 | | | 5,218 | 1 | STK |
| I6KLM125VB300 | 125 | 308 | | | 5,455 | 1 | STK |
| I6KLM125VB400 | 125 | 408 | | | 5,691 | 1 | STK |
| I6KLM125VB450 | 125 | 450 | | | 5,809 | 1 | STK |
| I6KLM125VB500 | 125 | 508 | | | 5,927 | 1 | STK |
| I6KLM125VB600 | 125 | 608 | | | 6,163 | 1 | STK |
| I6KLM125VB750 | 125 | 750 | | | 6,518 | 1 | STK |
| I6KLM125VB800 | 125 | 800 | | | 6,636 | 1 | STK |
| I6KLM125VB900 | 125 | 900 | | | 6,872 | 1 | STK |
| I6KLM125VB1000 | 125 | 1000 | | | 7,109 | 1 | STK |

Fix with:



Round head
square neck bolt
(DIN 603)
I6RBK

Nut (DIN 934)
I6M

Minimum number bolts and nuts: 8 pieces.

Pickled and passivated.



Giant washer
(DIN 125-1 A)
I6RO