


# I6KLZT

## T-piece for I6KLZ



Radius: 600 mm

|   |      |      |      |      |      |
|---|------|------|------|------|------|
|   | 200  | 300  | 400  | 500  | 600  |
| A | 1962 | 2062 | 2162 | 2262 | 2362 |

### Fix with:



Round head square neck bolt (DIN 603)  
I6RBK

Nut (DIN 934)  
I6M

| Reference        | ↑<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Unit |
|------------------|---------|---------|------------|---------|--------|---|------|
| <b>I6KLZT200</b> | 150     | 208     |            |         | 16,934 | 1 | STK  |
| <b>I6KLZT300</b> | 150     | 308     |            |         | 18,394 | 1 | STK  |
| <b>I6KLZT400</b> | 150     | 408     |            |         | 19,707 | 1 | STK  |
| <b>I6KLZT500</b> | 150     | 508     |            |         | 21,020 | 1 | STK  |
| <b>I6KLZT600</b> | 150     | 608     |            |         | 20,921 | 1 | STK  |

Minimum number bolts and nuts: 12 pieces.

Pickled and passivated.



Giant washer (DIN 125-1 A)  
I6RO