

COMEGACLU290

Open suspension bracket universal



Useful for direct mounting to the ceiling or with threaded rod TIM8 or TIM10.

| | Max. load (in daN) | A |
|------------------|--------------------|-----|
| COMEGACLU290.100 | 70 | 145 |
| COMEGACLU290.150 | 60 | 145 |
| COMEGACLU290.200 | 60 | 145 |
| COMEGACLU290.250 | 50 | 195 |
| COMEGACLU290.300 | 50 | 195 |
| COMEGACLU290.400 | 40 | 245 |

| Reference | Finish | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|---------------------------|--------|---------|---------|------------|---------|--------|----|------|
| ZMCOMEGACLU290.100 | DF | 290 | 145 | 1,5 | | 0,520 | 12 | STK |
| ZMCOMEGACLU290.200 | DF | 290 | 245 | 1,5 | | 0,620 | 12 | STK |
| ZMCOMEGACLU290.250 | DF | 290 | 295 | 1,5 | | 0,760 | 6 | STK |
| ZMCOMEGACLU290.300 | DF | 290 | 345 | 1,5 | | 0,820 | 6 | STK |
| ZMCOMEGACLU290.400 | DF | 290 | 445 | 1,5 | | 0,930 | 6 | STK |

Fixing of the cable tray by VM6.20.

Use the VOMEGA to avoid compression of the profile.

Max. load (in daN): uniformly distributed over complete width of cantilever brackets.

Legend finish

- DF = Defender