

I6KLM100VSB

Courbe articulée pour I6KLM100



Coulisse au longeron extérieurement
Pré-assemblé.

| Référence | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|------------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM100VSB150 | 100 | 150 | | | 8,263 | 1 | STK |
| I6KLM100VSB200 | 100 | 218 | | 1135 | 8,381 | 1 | STK |
| I6KLM100VSB300 | 100 | 318 | | 1135 | 8,617 | 1 | STK |
| I6KLM100VSB400 | 100 | 418 | | 1135 | 8,854 | 1 | STK |
| I6KLM100VSB450 | 100 | 450 | | | 8,972 | 1 | STK |
| I6KLM100VSB500 | 100 | 518 | | 1135 | 9,089 | 1 | STK |
| I6KLM100VSB600 | 100 | 618 | | 1135 | 9,325 | 1 | STK |
| I6KLM100VSB750 | 100 | 750 | | | 9,562 | 1 | STK |
| I6KLM100VSB800 | 100 | 800 | | | 9,798 | 1 | STK |
| I6KLM100VSB900 | 100 | 900 | | | 10,035 | 1 | STK |
| I6KLM100VSB1000 | 100 | 1000 | | | 10,271 | 1 | STK |

A fixer avec:



Rondelle (DIN
125-1 A)
I6RO



Erou (DIN 934)
I6M



Boulon à collet
I6RBK

Nombre minimal des boulons et des écrous: 8 pièces.

Décapé et passivé.