


# I6KLM125VB

## Courbe extérieure pour I6KLM125



Rayon: 600 mm

Référence	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unité
<b>I6KLM125VB150</b>	125	150			5,100	1	STK
<b>I6KLM125VB200</b>	125	208			5,218	1	STK
<b>I6KLM125VB300</b>	125	308			5,455	1	STK
<b>I6KLM125VB400</b>	125	408			5,691	1	STK
<b>I6KLM125VB450</b>	125	450			5,809	1	STK
<b>I6KLM125VB500</b>	125	508			5,927	1	STK
<b>I6KLM125VB600</b>	125	608			6,163	1	STK
<b>I6KLM125VB750</b>	125	750			6,518	1	STK
<b>I6KLM125VB800</b>	125	800			6,636	1	STK
<b>I6KLM125VB900</b>	125	900			6,872	1	STK
<b>I6KLM125VB1000</b>	125	1000			7,109	1	STK

### A fixer avec:



Boulon à collet  
I6RBK

Ecrou (DIN 934)  
I6M



Rondelle (DIN  
125-1 A)  
I6RO

Nombre minimal des boulons et des écrous: 8 pièces.

Décapé et passivé.