

I6KLM125VSB

Courbe articulée pour I6KLM125



Coulisse au longeron extérieurement
Pré-assemblé.

| Référence | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|------------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM125VSB150 | 125 | 150 | | | 10,337 | 1 | STK |
| I6KLM125VSB200 | 125 | 218 | | 1135 | 10,455 | 1 | STK |
| I6KLM125VSB300 | 125 | 318 | | 1135 | 10,692 | 1 | STK |
| I6KLM125VSB400 | 125 | 418 | | 1135 | 10,928 | 1 | STK |
| I6KLM125VSB450 | 125 | 450 | | | 11,046 | 1 | STK |
| I6KLM125VSB500 | 125 | 518 | | 1135 | 11,164 | 1 | STK |
| I6KLM125VSB600 | 125 | 618 | | 1135 | 11,400 | 1 | STK |
| I6KLM125VSB750 | 125 | 750 | | | 11,636 | 1 | STK |
| I6KLM125VSB800 | 125 | 800 | | | 11,873 | 1 | STK |
| I6KLM125VSB900 | 125 | 900 | | | 12,109 | 1 | STK |
| I6KLM125VSB1000 | 125 | 1000 | | | 12,346 | 1 | STK |

A fixer avec:



Boulon à collet
I6RBK

Erou (DIN 934)
I6M



Rondelle (DIN
125-1 A)
I6RO

Nombre minimal des boulons et des écrous: 8 pièces.

Décapé et passivé.