

# VS

## Réduction



### A fixer avec:



Boulon et écrou  
autobloquant  
VM



Écrou  
autobloquant et  
boulon à collet  
VMK


Sur demande: Hauteur 35 mm - 85 mm - 110 mm (seulement en SZ et HD)

Référence	Finition	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unité
<b>ZMVS110.025</b>	DF	110	25	0,75	200	0,108	1	STK
<b>ZMVS110.050</b>	DF	110	50	0,75	200	0,121	1	STK
<b>ZMVS110.075</b>	DF	110	75	0,75	200	0,135	1	STK
<b>ZMVS110.100</b>	DF	110	100	0,75	200	0,149	1	STK
<b>ZMVS110.125</b>	DF	110	125	0,75	200	0,163	1	STK
<b>ZMVS110.150</b>	DF	110	150	0,75	200	0,176	1	STK
<b>ZMVS110.200</b>	DF	110	200	0,75	200	0,204	1	STK
<b>ZMVS110.250</b>	DF	110	250	0,75	200	0,231	1	STK
<b>ZMVS110.300</b>	DF	110	300	0,75	200	0,259	1	STK
<b>ZMVS110.350</b>	DF	110	350	0,75	200	0,286	1	STK
<b>ZMVS110.400</b>	DF	110	400	0,75	200	0,314	1	STK
<b>ZMVS85.025</b>	DF	85	25	0,75	200	0,081	1	STK
<b>ZMVS85.050</b>	DF	85	50	0,75	200	0,091	1	STK
<b>ZMVS85.075</b>	DF	85	75	0,75	200	0,101	1	STK
<b>ZMVS85.100</b>	DF	85	100	0,75	200	0,112	1	STK
<b>ZMVS85.125</b>	DF	85	125	0,75	200	0,122	1	STK
<b>ZMVS85.150</b>	DF	85	150	0,75	200	0,132	1	STK
<b>ZMVS85.200</b>	DF	85	200	0,75	200	0,153	1	STK
<b>ZMVS85.250</b>	DF	85	250	0,75	200	0,173	1	STK
<b>ZMVS85.300</b>	DF	85	300	0,75	200	0,194	1	STK
<b>ZMVS85.350</b>	DF	85	350	0,75	200	0,215	1	STK
<b>ZMVS85.400</b>	DF	85	400	0,75	200	0,235	1	STK
<b>ZMVS60.025</b>	DF	50	25			0,088	1	STK
<b>ZMVS60.050</b>	DF	50	50			0,088	1	STK
<b>ZMVS60.075</b>	DF	50	75			0,099	1	STK
<b>ZMVS60.100</b>	DF	50	100			0,110	1	STK
<b>ZMVS60.125</b>	DF	50	125			0,110	1	STK
<b>ZMVS60.150</b>	DF	50	150			0,121	1	STK
<b>ZMVS60.200</b>	DF	50	200			0,132	1	STK
<b>ZMVS60.250</b>	DF	50	250			0,154	1	STK
<b>ZMVS60.300</b>	DF	50	300			0,198	1	STK
<b>ZMVS60.350</b>	DF	50	350			0,198	1	STK
<b>ZMVS60.400</b>	DF	50	400			0,231	1	STK


Nombre minimal des boulons et des écrous: 4 pièces.

### Légende de la finition

- DF = Defender



1 x VS hx100



2 x VS hx050