

VS


Réduction



A fixer avec:



Boulon et écrou
autobloquant
VM



Écrou
autobloquant et
boulon à collet
VMK


Sur demande: Hauteur 35 mm - 85 mm - 110 mm (seulement en SZ et HD)

| Référence | Finition | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|--------------------|----------|---------|---------|------------|---------|--------|---|-------|
| ZMVS110.025 | DF | 110 | 25 | 0,75 | 200 | 0,108 | 1 | STK |
| ZMVS110.050 | DF | 110 | 50 | 0,75 | 200 | 0,121 | 1 | STK |
| ZMVS110.075 | DF | 110 | 75 | 0,75 | 200 | 0,135 | 1 | STK |
| ZMVS110.100 | DF | 110 | 100 | 0,75 | 200 | 0,149 | 1 | STK |
| ZMVS110.125 | DF | 110 | 125 | 0,75 | 200 | 0,163 | 1 | STK |
| ZMVS110.150 | DF | 110 | 150 | 0,75 | 200 | 0,176 | 1 | STK |
| ZMVS110.200 | DF | 110 | 200 | 0,75 | 200 | 0,204 | 1 | STK |
| ZMVS110.250 | DF | 110 | 250 | 0,75 | 200 | 0,231 | 1 | STK |
| ZMVS110.300 | DF | 110 | 300 | 0,75 | 200 | 0,259 | 1 | STK |
| ZMVS110.350 | DF | 110 | 350 | 0,75 | 200 | 0,286 | 1 | STK |
| ZMVS110.400 | DF | 110 | 400 | 0,75 | 200 | 0,314 | 1 | STK |
| ZMVS85.025 | DF | 85 | 25 | 0,75 | 200 | 0,081 | 1 | STK |
| ZMVS85.050 | DF | 85 | 50 | 0,75 | 200 | 0,091 | 1 | STK |
| ZMVS85.075 | DF | 85 | 75 | 0,75 | 200 | 0,101 | 1 | STK |
| ZMVS85.100 | DF | 85 | 100 | 0,75 | 200 | 0,112 | 1 | STK |
| ZMVS85.125 | DF | 85 | 125 | 0,75 | 200 | 0,122 | 1 | STK |
| ZMVS85.150 | DF | 85 | 150 | 0,75 | 200 | 0,132 | 1 | STK |
| ZMVS85.200 | DF | 85 | 200 | 0,75 | 200 | 0,153 | 1 | STK |
| ZMVS85.250 | DF | 85 | 250 | 0,75 | 200 | 0,173 | 1 | STK |
| ZMVS85.300 | DF | 85 | 300 | 0,75 | 200 | 0,194 | 1 | STK |
| ZMVS85.350 | DF | 85 | 350 | 0,75 | 200 | 0,215 | 1 | STK |
| ZMVS85.400 | DF | 85 | 400 | 0,75 | 200 | 0,235 | 1 | STK |
| ZMVS60.025 | DF | 50 | 25 | | | 0,088 | 1 | STK |
| ZMVS60.050 | DF | 50 | 50 | | | 0,088 | 1 | STK |
| ZMVS60.075 | DF | 50 | 75 | | | 0,099 | 1 | STK |
| ZMVS60.100 | DF | 50 | 100 | | | 0,110 | 1 | STK |
| ZMVS60.125 | DF | 50 | 125 | | | 0,110 | 1 | STK |
| ZMVS60.150 | DF | 50 | 150 | | | 0,121 | 1 | STK |
| ZMVS60.200 | DF | 50 | 200 | | | 0,132 | 1 | STK |
| ZMVS60.250 | DF | 50 | 250 | | | 0,154 | 1 | STK |
| ZMVS60.300 | DF | 50 | 300 | | | 0,198 | 1 | STK |
| ZMVS60.350 | DF | 50 | 350 | | | 0,198 | 1 | STK |
| ZMVS60.400 | DF | 50 | 400 | | | 0,231 | 1 | STK |


Nombre minimal des boulons et des écrous: 4 pièces.

Légende de la finition

- DF = Defender



1 x VS hx100



2 x VS hx050