


KLM100SB45

Courbe intérieure à 45° pour KLM100

Rayon: 600 mm



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecoux elargi (DIN
6923)
RM

Référence	Finition	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Unité
KLM100SB45.150	SZ	100	158			2,724	1	STK
KLM100SB45.200	SZ	100	208			2,840	1	STK
KLM100SB45.300	SZ	100	308			3,070	1	STK
KLM100SB45.400	SZ	100	408			3,300	1	STK
KLM100SB45.450	SZ	100	458			3,416	1	STK
KLM100SB45.500	SZ	100	508			3,531	1	STK
KLM100SB45.600	SZ	100	608			3,761	1	STK
KLM100SB45.750	SZ	100	758			4,107	1	STK
KLM100SB45.800	SZ	100	808			4,222	1	STK
KLM100SB45.900	SZ	100	908			4,453	1	STK
KLM100SB45.1000	SZ	100	1008			4,683	1	STK
ZMKLM100SB45.150	DF	100	158			2,724	1	STK
ZMKLM100SB45.200	DF	100	208			2,840	1	STK
ZMKLM100SB45.300	DF	100	308			3,070	1	STK
ZMKLM100SB45.400	DF	100	408			3,300	1	STK
ZMKLM100SB45.450	DF	100	458			3,416	1	STK
ZMKLM100SB45.500	DF	100	508			3,531	1	STK
ZMKLM100SB45.600	DF	100	608			3,761	1	STK
ZMKLM100SB45.750	DF	100	758			4,107	1	STK
ZMKLM100SB45.800	DF	100	808			4,222	1	STK
ZMKLM100SB45.900	DF	100	908			4,453	1	STK
ZMKLM100SB45.1000	DF	100	1008			4,683	1	STK

Nombre minimal des boulons et des écrous: 8 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender