


KLM125VB45

Courbe extérieure pour KLM125

Rayon: 600 mm



A fixer avec:



Ecrou élargi (DIN
6923)
RM

Boulon à collet
(DIN 603)
RBK

Référence	Finition	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Unité
KLM125VB45.150	SZ	125	158			3,200	1	STK
KLM125VB45.200	SZ	125	208			3,276	1	STK
KLM125VB45.300	SZ	125	308			3,430	1	STK
KLM125VB45.400	SZ	125	408			3,584	1	STK
KLM125VB45.450	SZ	125	458			3,660	1	STK
KLM125VB45.500	SZ	125	508			3,737	1	STK
KLM125VB45.600	SZ	125	608			3,891	1	STK
KLM125VB45.750	SZ	125	758			4,121	1	STK
KLM125VB45.800	SZ	125	808			4,198	1	STK
KLM125VB45.900	SZ	125	908			4,352	1	STK
KLM125VB45.1000	SZ	125	1008			4,505	1	STK
ZMKLM125VB45.150	DF	125	158			3,200	1	STK
ZMKLM125VB45.200	DF	125	208			3,276	1	STK
ZMKLM125VB45.300	DF	125	308			3,430	1	STK
ZMKLM125VB45.400	DF	125	408			3,584	1	STK
ZMKLM125VB45.450	DF	125	458			3,660	1	STK
ZMKLM125VB45.500	DF	125	508			3,737	1	STK
ZMKLM125VB45.600	DF	125	608			3,891	1	STK
ZMKLM125VB45.750	DF	125	758			4,121	1	STK
ZMKLM125VB45.800	DF	125	808			4,198	1	STK
ZMKLM125VB45.900	DF	125	908			4,352	1	STK
ZMKLM125VB45.1000	DF	125	1008			4,505	1	STK

Nombre minimal des boulons et des écrous: 8 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender