


KLZVB

Courbe extérieure pour KLZ



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecoux elargi (DIN
6923)
RM

Rayon: 600 mm

Référence	Finition	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Unité
KLZVB150	-	150	150			5,856	1	STK
KLZVB200	SZ	150	208			5,971	1	STK
KLZVB300	SZ	150	308			6,202	1	STK
KLZVB400	SZ	150	408			6,432	1	STK
KLZVB600	SZ	150	608			6,893	1	STK
KLZVB800	-	150	800			7,354	1	STK
KLZVB1000	-	150	1000			7,815	1	STK
ZMKLZVB150	-		150			5,856	1	STK
ZMKLZVB200	DF	150	208			5,971	1	STK
ZMKLZVB300	DF	150	308			6,202	1	STK
ZMKLZVB400	DF	150	408			6,432	1	STK
ZMKLZVB500	DF	150	508			6,663	1	STK
ZMKLZVB600	DF	150	608			6,893	1	STK
ZMKLZVB800	-		800			7,354	1	STK
ZMKLZVB1000	-		1000			7,815	1	STK
PEKLZVB150	-	150	150			5,856	1	STK
PEKLZVB800	-	150	800			7,354	1	STK
PEKLZVB1000	-	150	1000			7,815	1	STK

Nombre minimal des boulons et des écrous: 8 pièces.

Légende de la finition

- SZ = Sendzimir
- DF = Defender