


## OBG

### Etrier de montage à l'extérieur



|              |                      |
|--------------|----------------------|
| Exec. Std.   | Sendzimir            |
| Mat. Opt.    | Galvanisé à chaud    |
| Mat. Opt. PE | Revêtement en poudre |

|        | Charge Maximale (daN) |
|--------|-----------------------|
| OBG050 | 200                   |
| OBG075 | 200                   |
| OBG100 | 200                   |
| OBG150 | 200                   |
| OBG200 | 200                   |
| OBG250 | 150                   |
| OBG300 | 150                   |
| OBG400 | 90                    |

| HD | Référence     | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk |  | Magasin | Unité |
|----|---------------|---------|---------|------------|---------|--------|---|---------|-------|
| HD | <b>OBG050</b> | 64      | 55      |            |         | 0,100  | 12  | X       | STK   |
| HD | <b>OBG075</b> | 64      | 80      |            |         | 0,130  | 12  | X       | STK   |
| HD | <b>OBG100</b> | 64      | 105     |            |         | 0,140  | 12  | X       | STK   |
| HD | <b>OBG150</b> | 64      | 155     |            |         | 0,190  | 12  | X       | STK   |
| HD | <b>OBG200</b> | 64      | 205     |            |         | 0,220  | 12  | X       | STK   |
| HD | <b>OBG250</b> | 64      | 255     |            |         | 0,270  | 12  | X       | STK   |
| HD | <b>OBG300</b> | 64      | 305     |            |         | 0,310  | 6   | X       | STK   |
| HD | <b>OBG400</b> | 64      | 405     |            |         | 0,390  | 6   | X       | STK   |

A commander par emballage complet.  
A fixer avec tige filetée TIM8 ou TIM10.