



# ZCL

## Z-support encliquetable



|            |                   |
|------------|-------------------|
| Exec. Std. | Sendzimir         |
| Mat. Opt.  | Galvanisé à chaud |

|        | Charge Maximale (daN) |
|--------|-----------------------|
| ZCL100 | 150                   |
| ZCL150 | 150                   |
| ZCL200 | 120                   |
| ZCL300 | 105                   |
| ZCL400 | 90                    |
| ZCL500 | 80                    |
| ZCL600 | 65                    |

| HD | Référence     | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦  | Magasin | Unité |
|----|---------------|---------|---------|------------|---------|--------|----|---------|-------|
| HD | <b>ZCL100</b> | 14      | 60      |            | 180     | 0,135  | 12 | X       | STK   |
| HD | <b>ZCL150</b> | 14      | 60      |            | 230     | 0,165  | 12 | X       | STK   |
| HD | <b>ZCL200</b> | 14      | 60      |            | 280     | 0,210  | 12 | X       | STK   |
| HD | <b>ZCL300</b> | 14      | 60      |            | 380     | 0,265  | 12 | X       | STK   |
| HD | <b>ZCL400</b> | 14      | 60      |            | 480     | 0,315  | 12 | X       | STK   |
| HD | <b>ZCL500</b> | 14      | 60      |            | 580     | 0,365  | 12 | X       | STK   |
| HD | <b>ZCL600</b> | 14      | 60      |            | 680     | 0,415  | 12 | X       | STK   |

A commander par emballage complet.