


## E Embout



Sur demande: Hauteur 35 mm - 85 mm - 110 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE


Revêtement en poudre

HD	Référence	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	<b>E60.050</b>	55	46			0,107	1	X	STK
-	<b>E60.075</b>	55	71			0,118	1	X	STK
-	<b>E60.100</b>	55	96			0,129	1	X	STK
-	<b>E60.150</b>	55	146			0,151	1	X	STK
-	<b>E60.200</b>	55	196			0,173	1	X	STK
-	<b>E60.300</b>	55	296			0,217	1	X	STK
-	<b>E60.400</b>	55	396			0,261	1	X	STK
-	<b>E60.500</b>	55	496			0,305	1	X	STK
-	<b>E60.600</b>	55	596			0,349	1	X	STK
-	<b>ZME60.050</b>	55	46			0,099	1	X	STK
-	<b>ZME60.075</b>	55	46			0,11	1	X	STK
-	<b>ZME60.100</b>	55	96			0,121	1	X	STK
-	<b>ZME60.150</b>	55	146			0,143	1	X	STK
-	<b>ZME60.200</b>	55	196			0,154	1	X	STK
-	<b>ZME60.300</b>	55	296			0,198	1	X	STK
-	<b>ZME60.400</b>	55	396			0,242	1	X	STK
-	<b>ZME60.500</b>	55	496			0,286	1	X	STK
-	<b>ZME60.600</b>	55	596			0,33	1	X	STK

### A fixer avec:



Boulon et écrou  
autobloquant  
VM



Écrou  
autobloquant et  
boulon à collet  
VMK

Nombre minimal des boulons et des écrous: 4 pièces.