


E

Embout



Sur demande: Hauteur 35 mm - 85 mm - 110 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE


Revêtement en poudre

HD	Référence	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	E60.050	55	46			0,107	1	X	STK
-	E60.075	55	71			0,118	1	X	STK
-	E60.100	55	96			0,129	1	X	STK
-	E60.150	55	146			0,151	1	X	STK
-	E60.200	55	196			0,173	1	X	STK
-	E60.300	55	296			0,217	1	X	STK
-	E60.400	55	396			0,261	1	X	STK
-	E60.500	55	496			0,305	1	X	STK
-	E60.600	55	596			0,349	1	X	STK
-	ZME60.050	55	46			0,099	1	X	STK
-	ZME60.075	55	46			0,11	1	X	STK
-	ZME60.100	55	96			0,121	1	X	STK
-	ZME60.150	55	146			0,143	1	X	STK
-	ZME60.200	55	196			0,154	1	X	STK
-	ZME60.300	55	296			0,198	1	X	STK
-	ZME60.400	55	396			0,242	1	X	STK
-	ZME60.500	55	496			0,286	1	X	STK
-	ZME60.600	55	596			0,33	1	X	STK

A fixer avec:



Boulon et écrou
autobloquant
VM



Écrou
autobloquant et
boulon à collet
VMK

Nombre minimal des boulons et des écrous: 4 pièces.