


# SB90

## Courbe concave VI à 90°



Emboîtable avec le chemin de câbles

Rayon: 100 mm

Sur demande: Hauteur 35 mm - 85 mm - 110 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE


Revêtement en poudre

HD	Référence	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	<b>SB90.60.050</b>	60	50			0,550	1	X	STK
-	<b>SB90.60.075</b>	60	75			0,650	1	X	STK
-	<b>SB90.60.100</b>	60	100			0,730	1	X	STK
-	<b>SB90.60.150</b>	60	150			0,880	1	X	STK
-	<b>SB90.60.200</b>	60	200			1,000	1	X	STK
-	<b>SB90.60.300</b>	60	300			1,180	1	X	STK
-	<b>SB90.60.400</b>	60	400			1,430	1	X	STK
-	<b>SB90.60.500</b>	60	500			1,900	1	X	STK
-	<b>SB90.60.600</b>	60	600			2,150	1	X	STK
-	<b>ZMSB90.60.050</b>	60	50			0,55	1		STK
-	<b>ZMSB90.60.075</b>	60	75			0,65	1		STK
-	<b>ZMSB90.60.100</b>	60	100			0,73	1		STK
-	<b>ZMSB90.60.150</b>	60	150			0,88	1		STK
-	<b>ZMSB90.60.200</b>	60	200			1	1		STK
-	<b>ZMSB90.60.300</b>	60	300			1,18	1		STK
-	<b>ZMSB90.60.400</b>	60	400			1,43	1		STK
-	<b>ZMSB90.60.500</b>	60	500			1,9	1		STK
-	<b>ZMSB90.60.600</b>	60	600			2,15	1		STK

### A fixer avec:



Boulon et écrou  
autobloquant  
VM



Écrou  
autobloquant et  
boulon à collet  
VMK

Nombre minimal des boulons et des écrous: 8 pièces.