


VB90

Courbe convexe VE à 90°



Emboîtable avec le chemin de câbles

Rayon: 100 mm

Sur demande: Hauteur 35 mm - 85 mm - 110 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE


Revêtement en poudre

HD	Référence	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	VB90.60.050	60	50			0,550	1	X	STK
-	VB90.60.075	60	75			0,630	1	X	STK
-	VB90.60.100	60	100			0,650	1	X	STK
-	VB90.60.150	60	150			0,780	1	X	STK
-	VB90.60.200	60	200			0,850	1	X	STK
-	VB90.60.300	60	300			1,080	1	X	STK
-	VB90.60.400	60	400			1,330	1	X	STK
-	VB90.60.500	60	500			1,430	1	X	STK
-	VB90.60.600	60	600			1,600	1	X	STK
-	ZMVB90.60.050	60	50			0,55	1		STK
-	ZMVB90.60.075	60	75			0,63	1		STK
-	ZMVB90.60.100	60	100			0,65	1		STK
-	ZMVB90.60.150	60	150			0,78	1		STK
-	ZMVB90.60.200	60	200			0,85	1		STK
-	ZMVB90.60.300	60	300			1,08	1		STK
-	ZMVB90.60.400	60	400			1,33	1		STK
-	ZMVB90.60.500	60	500			1,43	1		STK
-	ZMVB90.60.600	60	600			1,6	1		STK

A fixer avec:



Boulon et écrou
autobloquant
VM



Écrou
autobloquant et
boulon à collet
VMK

Nombre minimal des boulons et des écrous: 8 pièces.